

Gas at 68°F

Adj for Air

PSI	BTU/Hr	Lbs./Hr	Ratio	BTU/Hr
0.84	16145	0.81	14.99	15388
2.18	26945	1.35	14.97	25644
4.10	37802	1.90	14.94	35897
6.53	48735	2.44	14.89	46145
9.41	59768	3.00	14.84	56387
12.68	70922	3.56	14.78	66620
16.27	82217	4.12	14.70	76845
20.13	93675	4.70	14.62	87060
24.22	105315	5.28	14.53	97263
<hr/>				
28.00	115842	5.81	14.17	104321
30.00	121268	6.07	13.83	106634
35.00	134834	6.75	13.07	111998
40.00	148400	7.43	12.41	117055
45.00	161966	8.11	11.83	121848

ATM	KW (fuel)	Kg/Hr	Efficiency Ratio	92.4% KW (net)
0.06	4730	0.37	14.99	4508
0.15	7894	0.61	14.97	7513
0.28	11074	0.86	14.94	10516
0.44	14277	1.11	14.89	13518
0.64	17509	1.36	14.84	16518
0.86	20777	1.61	14.78	19516
1.11	24086	1.87	14.70	22512
1.37	27442	2.13	14.62	25504
1.65	30852	2.40	14.53	28493
<hr/>				
1.91	33936	2.63	14.17	30561
2.04	35526	2.75	13.83	31238
2.38	39500	3.06	13.07	32810
2.72	43474	3.37	12.41	34291
3.06	47448	3.68	11.83	35695

