

LP Gas at 68°F

Adj for Air

PSI	BTU/Hr	Lbs./Hr	Ratio	BTU/Hr
0.65	29505	1.48	14.56	27316
1.70	49243	2.47	14.54	45522
3.23	69082	3.46	14.51	63722
5.22	89064	4.47	14.47	81913
7.65	109227	5.48	14.41	100092
10.47	129610	6.50	14.35	118257
13.64	150252	7.53	14.28	136406
17.10	171191	8.58	14.20	154536
20.82	192463	9.65	14.11	172645
23.00	204416	10.25	14.02	182180
25.00	215262	10.79	13.64	186601
30.00	242376	12.15	12.79	197117
35.00	269489	13.51	12.08	206966
40.00	296603	14.87	11.47	216245
45.00	323717	16.23	10.93	225033

Efficiency 89.7%				
ATM	KW (fuel)	Kg/Hr	Ratio	KW (net)
0.04	8643	0.67	14.56	8002
0.12	14426	1.12	14.54	13336
0.22	20238	1.57	14.51	18667
0.36	26091	2.03	14.47	23996
0.52	31998	2.48	14.41	29322
0.71	37969	2.95	14.35	34643
0.93	44016	3.42	14.28	39960
1.16	50150	3.89	14.20	45271
1.42	56382	4.38	14.11	50576
1.57	59884	4.65	14.02	53370
1.70	63061	4.90	13.64	54665
2.04	71004	5.51	12.79	57746
2.38	78947	6.13	12.08	60631
2.72	86890	6.75	11.47	63349
3.06	94833	7.36	10.93	65923

